

# PRODUCT DATA SHEET

## Avery Dennison® 777CF Cast Film

Issued: 07/2023

### Introduction

Avery Dennison® 777 Cast Films are a signmaker's everyday answer for all kinds of quality signage, indoors and outdoors – including applications over rivets and corrugations, and jobs requiring applied durability of up to 8 years. Avery Dennison® 777 Cast Films are available in a very extensive range of standard colors, including gloss, matt and metallic. All the colors are based on organic pigments, REACH compliant.

### Conversion

Avery Dennison® 777 Cast Film offers good weeding and cutting performance on a wide range of computer signmaking equipment. Avery Dennison® 777 Cast Film can be thermal transfer printed.

### Recommendations

Avery Dennison® 777 Cast Films offer a wide range of colours for:

- » Graphics on rigid-sided vehicles
- » Graphics on boats (above water level) and sports vehicles
- » Directional signage
- » Window graphics
- » Outdoor advertising
- » Point-of-sale and promotional uses

### Features

- » 100 standard stock colors with a glossy finished
- » Improved cutting and weeding
- » Excellent dimensional stability
- » Very good conformability to rivets and corrugations
- » Matched value for money
- » Outdoor durability upto 8 years outside
- » Up to 4 years clean removability (metallics excluded)
- » Outstanding choice of colours in gloss finish
- » The signmaker's 'one-stop shop' for even the most demanding tasks
- » REACH compliant – conforming to the latest environmental regulations
- » New imprint liner for easier manual conversion
- » Avery Dennison® 777 Cast Film White and White Matt are manufactured on a blue contrast backing paper for ease of conversion



#### Face Film

60 micron cast vinyl



#### Adhesive

Black, white and colours: iA-tech™, Permanent acrylic based

Metallic colours: Permanent acrylic based



#### Backing

one side coated white kraft paper, 135 g/m<sup>2</sup>



#### Durability

Up to 8 years outdoor (vertical exposure)



#### Shelf Life

2 years - stored at 22°C and 50-55% RH

## Physical Characteristics

	Test method <sup>1</sup>	Results	
<b>Product</b>			
Caliper, facefilm (micron)	ISO 534	60	
Caliper, facefilm + adhesive (micron)	ISO 534	85	
Gloss (GU)	ISO 2813, 20°	50	
Dimensional stability (mm max.)	FINAT FTM 14	0.20	
Shelf life (years)	Stored at 22° C/50-55 % RH	2	
Durability <sup>2</sup> (years)	Vertical exposure	Black&White - 8	
		All colors & Transparent - 7	
		Metallic - 5	
<b>Adhesive</b>		iA-tech™ permanent adhesive	Permanent adhesive
Elongation (%)	DIN 53455	120	120
Adhesion, initial (N/m)	FINAT FTM-1, stainless steel	400	400
Adhesion, after 24 hours (N/m)	FINAT FTM-1, stainless steel	520	520
<b>Temperature range</b>			
Application temperature (Minimum: °C)		+10	
Service temperature (°C to +°C)		-40 to +90	
<b>Chemical properties<sup>3</sup></b>			
Saltspray resistance	120 hours exposure	No effect	
Water resistance	48 hours immersion	No effect	

## Important

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

1) Test methods: More information about our test methods can be found on our website.

2) Durability: The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.

3) Prolonged immersion in gasoline and similar fluids is not recommended.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>.

Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

© 2023 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.