

# Blackboard ASLAN C 61

## Self-adhesive blackboard film for writing on with chalk

This self-adhesive blackboard film transforms a wide variety of rigid and smooth surfaces into a classic black chalkboard in an instant. You can write on it with chalk as often as you like without leaving any shadows or ghosting. In places like offices, nurseries, schools and restaurants, you can turn walls, furniture or doors into versatile blackboards for frequently changed messages. The self-adhesive film can be cut to any shape and size, as well as customised using UV-curing or screen printing inks.

For any further information please contact our technical advisory service:  
**+49 2204.708-80**

## Construction

face-film:	PVC	
thickness:	~ 160 µm	
adhesive:	pressure sensitive polyacrylate adhesive	thickness: ~ 25 g/m <sup>2</sup>
release liner:	silicone paper	square weight: ~ 63 g/m <sup>2</sup>

## Characteristics

adhesive strength: (ASTMD-903)	immediately: after 1 week:	~ 6 N/25 mm ~10 N/25 mm
dimensional stability:	applied onto acrylic glass after 24 hours at 70 °C	insignificant longitudinal shrinkage
temperature:	application temperature: service temperature range:	min. 15°C -30 °C up to +80 °C
combustibility:	Stuck on aluminum, the film is self-extinguishing	
durability:	up to 2 years outdoors, with vertical exposure, in central European standard climatic conditions	

### ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany

phone +49 (0) 2204.708 80 · fax +49 (0) 2204.708 50

e-mail [info@ASLAN-Schwarz.com](mailto:info@ASLAN-Schwarz.com)



[www.ASLAN-Schwarz.com](http://www.ASLAN-Schwarz.com)

**ASLAN**

EXPERTISE IN SELF-ADHESIVE FILMS

# Blackboard ASLAN C 61

## Processing

---

- printability:** The material is digitally printable with UV-curing inks as well as with screen printing inks. When using screen printing inks, the print has to dry for at least 48 hours before processing it.
- application:** Application dry or wet. If applied wet, a whitening of the adhesive can occur, but will disappear after a couple of days depending on the weather conditions.
- For a wet application we recommend the transfer liquid ASLAN TL10.
- storage life:** Before application the films can be stored for minimum 3 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60 %. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either standing vertical or on 'hanging' racks designed for this purpose.

---

**State:** 03|2015

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

---

**ASLAN, Schwarz GmbH & Co. KG**

Oberauel 2 · 51491 Overath · Germany

**phone** +49(0)2204.708 80 · **fax** +49(0)2204.708 50

**e-mail** [info@ASLAN-Schwarz.com](mailto:info@ASLAN-Schwarz.com)



[www.ASLAN-Schwarz.com](http://www.ASLAN-Schwarz.com)

**ASLAN**<sup>®</sup>

EXPERTISE IN SELF-ADHESIVE FILMS