

APEX PREMIUM CANVAS METALIC SILVER POLYESTER 220G

Eco-Solvent Silver Polyester Canvas

Performance and Parameters

Property	Typical Value	Standard
Material	100% Polyester	DIN 60001,ASTM D7641
Yarn	300D*300D	DIN EN ISO 2060,ASTM D1907
Weave Method	Woven	---
Weight	220±20gsm	ISO536
Thickness	260±30µm	ISO534
Opacity	>90%	ISO2471
Color	L*:70.0±2.0; a*:-1.0±2.0; b*:0±2.0	---
Application	Decorative Painting,Canvas,Exhibition Painting	---

Size

Width	1.067 m/1.27m /1.524 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	30 m/50 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Compatible Inks

Eco-Solvent	Solvent	UV	Latex
√	√	√	√

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Important:

Before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.