

Technical information:

## Apex Premium Printing Floor, 800 g/m<sup>2</sup>, wykładzina PET/PCW

ITEM	DATA	UNIT	TEST METHOD
<b>fabric</b>	high tenacity yarns 100%PES		DIN EN ISO2060
<b>construction</b>	weaving: 500*500 28*28	inch	DIN60001
<b>total weight</b>	800 gsm	g/sqm	DIN53352 BS3424 method5A
<b>fabric weight</b>	150 gsm	g/sqm	
<b>PVC coating weight</b>	650 gsm	g/sqm	
<b>tensile strength</b>	warp: 1700	N/5cm	DIN53354 BS3424 method6A
	weft: 1 800		
<b>tearing strength</b>	warp: 170	N	DIN53356 BS3424 method 7A
	weft: 160		
<b>adhesion</b>	80	N/5cm	DIN53357 BS3425 method9B
<b>suitable temperature</b>	-20 -----+70	°C	DIN 53372 BS3424 method10

The indexes above are on average, so there will be ±5% tolerance for actual material.

The information contained in the product data sheet is based on practical knowledge and experience and should be used only as a source of information and does not constitute a legal guarantee of specific features. All information provided is for product description only and should not be considered as guaranteed properties in a legal sense. Due to the very large number of possible applications, the user should test the material for his own needs before final use. The buyer bears all risks associated with the use, handling and application of the material. We are liable for damages only up to the purchase price, excluding indirect and incidental damages.