# Technical information: **SteikoTex Flag 110 FR**

| PROPERTIES | DATA | TEST METHOD |
|---|---|---|
| **surface** | semi-matte | N/A |
| **total weight** | 110 g/m2 | DIN EN ISO 2286-2, ASTM D751 |
| **base fabric** | 100% polyester | DIN 60001, ASTM D7641 |
| **weave method** | warp-knitted | N/A |
| **shrinkage** | ≤2% | 210 ℃, 30s |
| **flame resistance** | B1 | DIN 4102-15&16 |
| **recommend fixation temperature** | 190℃-210℃, 1-2min | N/A |
| **yellowing temperature** | ≥210℃ | SUPRKC REX-C400, 30s |
| **rolls** | 1,10 / 1,60 / 1,83 / 2,15 x 100 m | |
| **INK printability** | DYE direct / DYE paper | |

**NOTE: It is normal that the weight of most products will have an average fluctuation of 5%.**

The information contained in the product data sheet is based on practical knowledge and experience and should be used only as a source of information and does not constitute a legal guarantee of specific features. All information provided is for product description only and should not be considered as guaranteed properties in a legal sense. Due to the very large number of possible applications, the user should test the material for his own needs before final use. The buyer bears all risks associated with the use, handling and application of the material. We are liable for damages only up to the purchase price, excluding indirect and incidental damages.