

APEX PREMIUM EASY STICK FR HIGH OPACITY 115g

PRODUCT DESCRIPTION:

Film:150d*150d 115gsm woven Polyester

Color:White

Surface:Matt

APPLICATION

Applying on the glossy, smooth surfaces. Eggshell Paints etc walls.

PRINTING METHOD:

Compatible with Solvent Ink, Eco-solvent, Latex, and UV Curable Inks

TECHNICAL DATA:

| CHARACTERISTIC | TEST METHOD | AVERAGE VALUES |
|------------------------------------|---------------|---|
| Film Weight | ISO 4591:1992 | 150d*150d 115gsm woven Polyester |
| Adhesive type | | 100% Removable Solvent Glue, Repositionable |
| Release paper | | Embossed 140 gsm Double Sides PE-Coated Silicon Paper |
| Dimensional stability | FINAT TM14 | Adhered to steel, 0.2mm in cross direction, in length 0.50mm max. |
| Temperature resistance | | Adhered to aluminum. -20°C to +100°C, no variation |
| Seawater resistance | DIN 50021 | Adhered to glass, after 48h/23°C no variation |
| Adhesive power | FINAT TM1 | After 24h, stainless steel 3-7N/25mm |
| All of the weight of the materials | | 340gsm |
| Thickness of all the material | | 330microns |
| Shelf life | | 1 year |
| Storage | | One year out of direct sunlight at 23°C and 50% humidity |
| Application temperature | | Min.+10°C |
| Weathering | | 2 year |

Attention: After printing the ink must be thoroughly dry in order to avoid any affect on the later combination with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.