

## APEX PREMIUM TEXTIL SATIN 220g

### Flocking Silky Wall Covering Fabric

#### Performance and Parameters

Property	Typical Value	Standard
Material	100%Polyester	DIN 60001,ASTM D7641
Weave method	Woven	--
Weight	220±5%g/sq.m, 6.4±5%oz/sq.yd	ISO536
Thickness	310±30	ISO534
Opacity	>90%	ISO2471
Whiteness	150±10	ISO11475
Gloss [60°]	6-10	GB/T 9754-2007
Application	Mural,Wall Covering	--

#### Size

Width	42" /50" /60"/90"/98"/110"/118"/126"	Standard	DIN EN ISO 3759,ASTM D751-2006
Length	50m/60m	Standard	DIN EN ISO 3759,ASTM D751-2006

#### Compatible Inks

Solvent	Eco-Solvent	Latex	UV
✓	✓	✓	✓

#### Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

#### Important:

Before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.