

APEX PREMIUM TEXTIL SHINING 240g

Flocking Shining Wall Covering Fabric

Performance and Parameters

| Property | Typical Value | Standard |
|--------------|------------------------------|-----------------------|
| Material | 100% Polyester | DIN 60001, ASTM D7641 |
| Weave method | Woven | -- |
| Weight | 235±5%g/sq.m, 6.9±5%oz/sq.yd | ISO536 |
| Thickness | 380±30 | ISO534 |
| Opacity | >90% | ISO2471 |
| Whiteness | 150±10 | ISO11475 |
| Gloss [60°] | 3-4 | GB/T 9754-2007 |
| Application | Mural, Wall Covering | -- |

Size

| | | | |
|--------|--------------------------------------|----------|---------------------------------|
| Width | 42" /50" /60"/90"/98"/110"/118"/126" | Standard | DIN EN ISO 3759, ASTM D751-2006 |
| Length | 50m/60m | Standard | DIN EN ISO 3759, ASTM D751-2006 |

Compatible Inks

| Solvent | Eco-Solvent | Latex | UV |
|---------|-------------|-------|----|
| ✓ | ✓ | ✓ | ✓ |

Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Important:

Before using the media the user must examine the suitability of the media for each application. We shall not assume liability for non-performance of the media. Specifications are subject to change without notice.