



A POLI-TAPE GROUP Company

DIGIT 150 CLING Transparent Gloss

Product Information

Monomeric, electrostatic PVC (transparent gloss, 150 μ) laminated on an one-sided PE-pasteboard liner (180 g/m²).

The PVC offers a high dimensional stability.

Especially designed for short-term window decoration.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

Technical Data

| | |
|---------------------------------|---|
| Carrier: | monomeric, electrostatic PVC, (cling-film) |
| Thickness: | 150 μ +/- 5 % |
| Adhesive: | ./. |
| Adhesion: | ./. |
| Liner: | one-sided PE-pasteboard (180 g/m ²) |
| Application temperature: | +10 - +40 °C |
| Service temperature: | - 20 - +50 °C |
| Outdoor durability: | 1 year (unprinted film) |

Standard Dimensions

1000 mm x 50 m

1370 mm x 50 m

KEMICA S.r.l.

Via F.Ili Rusjan, 76 - Frazione Rupa
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501

Fax: +39 0481 882 440

E-Mail: info@kemicasrl.it

Internet: www.kemica.it

30/08/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.